



This is the smallest Fisher dolly, compact "lightweight" and maneuverable. The Dolly 11 has similar characteristics and operating as Dolly 10. This Fisher dolly is designed and produced to meet the demands of both the film and television industry. The compact size, the three-way control and the very stable lift arm provides a wide and flexible deployment. The Fisher dolly is reliable, quiet, smooth in operation and secure.

## SPECS

Max Payload	408.23 kg (900 lbs)
Dolly Length	1.02 m (3.35 ft)
Dolly Width	0.65 m (2.13 ft)
Dolly Weight	139.35 kg (306.99 lbs)
Max Lift Range	1299 mm (51.14 inch)
Min Lift Range	340 mm (13.39 inch)
Vertical Travel	847 mm (33.35 inch)

Power Requirement	220 V, 16 Amp
Internal Battery Power	No
Curved Track	Yes
Min Turn Circle	0.41 m (1.35 ft)
Track Size	620 mm (24.41 inch)
Head Fitting	Mitchel, Bowl, Elemac
Steering: Crab Mode	Yes
Steering: Round Mode	Yes
Steering: 2 Wheel Front	Yes
Steering: 2 Wheel Back	Yes
Electric Lift	No
Hydraulic Lift	No
Air Lift	Yes
	 <a href="#">productfiche</a> <a href="#">jlfischer11</a>