

Are you looking for a lightweight crane (JIB) which can be located at inaccessible locations? The Jimmy Jib is a solution.


The length of the jib can be determined on site, ranging from 1,80 meters till 12 meters. The Jib fits in 4 flighttubes and 2 pelicases, so everything can be easily transported worldwide.

Our Jimmy-Jibs are delivered standard with a length of 7,3 meters. Smaller is always possible (and sometimes even better).

We also offer the Jimmy Jib with the STYPE-kit. This makes it possible to automatically track the camera with the movements of the jib (auto-aiming).

SPECS

Max Payload (Head + Camera)	27 kg (59.52 lbs)
Max Length (Pivot to Front End)	12.19 m (40 ft)
Min Length (Pivot to Front End)	1.83 m (6 ft)
Rear Section Length (Pivot to Rear End)	2.8 m (9.19 ft)
Max Lens Height	14 m (45.93 ft)

Overslung	
Max Lens Height Underslung	13 m (42.65 ft)
Total Maximum Weight	700 kg (1543 lbs)
Footprint 360° Length	3,5 m (11,48ft) - 6 m (19,69ft)
Footprint 360° Width	3,5 m (11,48ft) - 6 m (19,69ft)
Footprint 180° Length	3,5 m (11,48ft) - 6 m (19,69ft)
Footprint 180° Width	2 m (6,56 ft) - 4,5 m (14,74ft)
Track Wheels	Yes
Track Size	620 mm (24.41 inch)
	 specs sheet