



The Panther Evolution is the standard among film dollies. The hydraulic column operates very smooth and delivers maximum stability. High-end wheels and PDC tracks provide the most stable travel-shots. Accessories like snake, low-bowl, U-Bangi, low-base platform, risers and super-jib II are all available to make the most extreme shots. The arms are retractable, to operate in very tight spots. On a studio-floor you can use this dolly on hard wheels, switchable between 2 and 4-wheel steering.

## SPECS

Max Payload	300 kg (661 lbs)
Dolly Length	0.84 m (2.76 ft)
Dolly Width	0.83 m (2.72 ft)
Dolly Weight	136 kg (300 lbs)
Max Lift Range	1360 mm (53.54 inch)
Min Lift Range	680 mm (26.77 inch)
Vertical Travel	680 mm (26.77 inch)

Power Requirement	220 V, 16 Amp
Internal Battery Power	No
Curved Track	Yes
Track Size	360 / 620 mm (14 / 24.5 inch)
Head Fitting	Mitchel, Bowl, Elemac, Custom
Steering: Crab Mode	Yes
Steering: Round Mode	No
Steering: 2 Wheel Front	Yes
Steering: 2 Wheel Back	Yes
Electric Lift	No
Hydraulic Lift	Yes
Air Lift	No
	 <a href="#">productfiche_pantherevolution_eng.pdf</a>