



The (r)evolution on using cranes in small spaces. Enables you to perform complex camera movements between obstacles that previously were not possible.

The Super Techno 15 fits through a standard door of 90 cm. All the advantages of a telescopic crane are now applicable for interior shots.

This crane comes with a Z-head by default, but can also be fitted with a gyro-stabilized head. In this configuration, the Techno 15 is mainly used for travel-shots from a pickup or low-rider.

**SPECS**

Max Payload (Head + Camera)	59 kg (130 lbs)
Max Length (Pivot to Front End)	4.21 m (13.81 ft)
Min Length (Pivot to Front End)	1.34 m (4.4 ft)
Rear Section Length (Pivot to Rear End)	1.64 m (5.38 ft)
Max Lens Height Underslung	4.57 m (14.99 ft)
Telescopic Travel	2.86 m (9.38 ft)
Telescopic Travel Speed	0.75 m/s (2.46 ft/s)
Dolly Length	1.11 m (3.64 ft)
Dolly Width	0.88 m (2.89 ft)
Total Maximum Weight	559 kg (1232 lbs)

Footprint 360° Length	4.5 m (14.76 ft)
Footprint 360° Width	4.5 m (14.76 ft)
Footprint 180° Length	4.5 m (14.76 ft)
Footprint 180° Width	2.5 m (8.2 ft)
Power Requirement	220 V, 16 Amp
Weather Proof	No
Raincover	Yes
Track Wheels	Yes
Track Size	880 mm (34.6 inch)